



# PIG<sup>®</sup> DrainBlocker<sup>®</sup> Drain Cover

## New Pig

One Pork Avenue  
Tipton, PA 16684-0304

[newpig.com](http://newpig.com)

North America:  
**1-800-468-4647**


Europe:  
**+31 (0)76 596 92 50**

UK:  
**0800 919 900**


Outside North America:  
**+1-814-684-0101**




1. Sweep the area surrounding the drain and remove debris to ensure a proper seal.




2. Remove the clear protective film from the product and save for reuse.




3. Place product over the drain, tacky side down, overlapping all sides of the drain by at least 3 inches.



4. For optimum sealing, apply pressure by walking on product edges.



5. Wash and thoroughly dry after use.



6. Wrap in protective film.

### Important Notes:

- This product forms a tight seal with smooth surfaces.
- Some chemicals will degrade this product. Refer to our online chemical resistance guide for information.
- If this product is used in a spill response effort involving incompatible liquids, it should be disposed of with other spill response materials.
- Do not store in high humidity, or where temperatures exceed 120°F.
- The flexibility and sealing functions diminish at temperatures below -30°F.
- Elvaloy top can become slippery when wet. Please use caution.

**NOTE:** Due to the nature of softer urethane, the physical properties of these products may change over time with exposure to certain environmental conditions like temperature, humidity and UV radiation. Typical product life expectancy is 5 years. Please inspect the stored product regularly to ensure it is in a usable state. See [newpig.com](http://newpig.com) for chemical compatibility and urethane care guidelines.

PIG, PIG logo are registered trademarks in USA and other countries. See [tm.newpig.com](http://tm.newpig.com)

502036 / 330726

**DO NOT  
THROW AWAY:**  
reapply this film for storage