



PIG Grippy Absorbent Mat

SPECIAL ADHESIVE BACKING

Sticks to floors and flat surfaces!

- Specially formulated, full-coverage adhesive backing holds tight but leaves no residue
- Peels up easily for quick changeouts
- Absorbs oils, coolants, solvents and water
- Poly backing creates a liquidproof barrier that keeps floors completely dry
- No curling or bunching — lies flat to reduce trip hazards
- Tough, spunbond top layer stands up to traffic; dark color hides grime



Stays put no matter what™



Scan this code to see it in action!

New Pig

One Pork Avenue
Tipton, PA 16684-0304

1-800-HOT-HOGS
newpig.com/grippy

New Pig 2012. All rights reserved. PIG and the PIG logo are trademarks of New Pig in the U.S. and other countries.

165852/269185

PIG Grippy Absorbent Mat

Step 1 — Surface Preparation

Make sure the surface you want to cover is clean, dry and free of oil and debris before installing Grippy Mat.

Step 2 — Application

Place Grippy Mat adhesive-side down on a horizontal or vertical surface. Starting at the center, press down on the mat, working out to the edges and pushing out any air bubbles or creases until it is smooth, flat and securely in place. Depending on the age, condition and smoothness of the surface, prolonged downward force may be required to achieve a uniformly satisfactory bond.

Step 3 — Repositioning and Removal

Grippy Mat can be picked up and reapplied as long as the surface is clean and dry. To pick it up, pinch an edge of the Grippy Mat with one finger under the bottom tacky side and the other finger on the top absorbent side. Peel up slowly at a 90-degree angle. Using this method will avoid separation of the top and bottom layers, as well as prevent any adhesive residue from being left behind.

NOTE: When using a degreaser to clean the surface prior to placing Grippy Mat, rinse the surface thoroughly with water and let dry. Cleaning or polishing products interfere with Grippy Mat's adhesion — be sure to wipe surfaces where these products are used with a solvent such as MEK, heptane or lacquer thinner to completely remove them. A second wipe with fresh solvent and a clean cloth may be necessary.

All adhesives have potential to lift finish coatings or paint depending on the condition of the surface, and a repainted or coated surface is more susceptible to damage. Grippy Mat is formulated to work with most industrial floor surfaces, but testing a 6" square piece in a noncritical area can help you judge suitability for your use and avoid any potential damage.

The stitching on the mat may begin to fray after an extended period of time or intense use, and may indicate that the mat is due for replacement. Fraying will not affect the absorbency or adhesion of the mat.

Product life varies depending on many factors, including type of use, level of liquid saturation and the frequency of foot and vehicle traffic. Grippy Mat is super tough, but it will eventually show wear. Replace the mat when it is worn or when the saturation level approaches the mat edges to avoid liquid seeping out of the mat and under the Grippy backing.

Grippy Mat is constructed with a **pressure-sensitive adhesive**, so the heavier the weight of objects on top of the mat, the greater the bond to the surface will become. Inspect the mat regularly to determine how long you can leave it down before removal becomes more difficult.

For a full listing of Grippy Mat products, visit newpig.com/grippy.



PIG Grippy Mat lies flat without curling, bunching or sliding.



Grippy Mat stands up to foot and light, wheeled traffic as well as equipment driveovers.



Grippy Mat is available in pads or rolls.



New Pig

One Pork Avenue
Tipton, PA 16684-0304

Still have questions? In North America contact us:

By Phone: **1-800-HOT-HOGS** (468-4647)

Online: **newpig.com**

Email: **hothogs@newpig.com**

165852/269185