

PIG Anti-Fatigue Matting

This report is offered as a guide and was developed from information which, to the best of New Pig's knowledge, was reliable and accurate. Due to variables and conditions of application beyond New Pig's control, none of the data shown in this guide is to be construed as a guarantee, expressed or implied. New Pig assumes no responsibility, obligation, or liability in conjunction with the use or misuse of the information.

PIG Anti-Fatigue Matting

Use & Care Instructions

Unboxing

Within a few days of receipt, rolled mats should be unrolled and laid flat. Some rubber mats may have an oily residue or sticky film on them. This releasing agent is inherent to molding mats and is not a defect. Simply wipe down with a mild detergent or degreaser.

Storage

Roll up and store mats in a dry area with moderate temperatures (55-95°F). Do NOT stand mats on end or place under heavy objects.

Cleaning

IMPORTANT! Do not use rotary scrubbers or other mechanical cleaners/scrubbers on mats. Do not use solvents, harsh detergents or alkalis.

Shake or broom-sweep dirt off matting daily. To reduce premature wear and potential slip hazards, be sure to periodically sweep the floor beneath mats to remove any dirt and debris that could get trapped underneath.

- **For Vinyl Matting** — Use a hose, pressure washer or damp mop in conjunction with a nonabrasive, water-based detergent. Let the mat dry completely before allowing foot traffic to resume.
- **For Rubber Matting** — Use a hose, pressure washer or gently scrub by hand in conjunction with a nonabrasive, water-based detergent. Let the mat dry completely before allowing foot traffic to resume. Grease proof/resistant mats used in kitchens or oily environments should be cleaned using a water-based detergent and degreaser and a mop or pressure washer to break up excessive grease. Mats should NOT be put in a dishwasher.
- **For Gritted Surface Matting** (including TuffGrit products) — Use a hose in conjunction with a mild surfactant or dish soap. For stubborn deposits, scrub with a stiff-bristle brush. Do NOT use mops. The gritted surface will catch and retain fibers from the mop.



New Pig

One Pork Avenue
Tipton, PA 16684-0304

newpig.com

North America: **1-800-468-4647**

Europe: **+31 (0)76 596 92 50**

China: **+86-21-400 921 5178**

PIG, PIG logo are registered trademarks in USA and other countries. See tm.newpig.com

UK: **0800 919 900**

Outside North America: **+1-814-684-0101**

502965 / 364724