

Aerosol Four-Can Recycler Installation and Use

Installation





1. Thread 4-can puncturing unit into 2" bung until support plate touches rim of drum.



2. Install the grounding wire.



3. Thread combination filter into ³/₄" bung. Press "power" button on Timestrip Indicator to start tracking 3-month service life.

Safety

- No smoking
- Always use outdoors or in a well-ventilated area; keep away from open flame
- Wear safety goggles (included with kit)
- Use on 55-gallon, closed-head steel drum only; drum must be in good condition
- Monitor filter life and replace as indicated (puncturing full cans will reduce the life of filter)
- Cover of puncturing unit should always contact the top of the cans before locking in place and puncturing
- DO NOT overfill drum; drum should be disposed of once 70% full
- DO NOT puncture full cans if drum is over 50% full
- DO NOT co-mingle corrosives, oxidizers and solvents; chemical reactions may generate heat and unsafe vapors
- DO NOT puncture powder sprays (may create static and self-ignite)

Operation



 Disengage and lower ratchet clamp on right side of puncturing unit. Unlock cam-lever clamp on left side of puncturing unit to slide cover up to the open position. Lock cam-lever clamp to hold lid in place.



2. Insert one domed can into each chamber of puncturing unit. All cans must be the same height.



3. Unlock cam-lever clamp to lower cover and close puncturing unit.



4. Raise ratchet clamp until it contacts cover, pull lever to tighten. Do not overtighten ratchet clamp (three clicks only). Press handle to raise pins and puncture cans. Lift handle after puncturing. Allow cans to fully drain. Remove cans and position cover back into fully closed position.

Maintenance

- Clean pins with a solvent after completion of each job
- Replace filter every three months as indicated on the Timestrip™ Indicator
- Replace gasket as needed to keep a good seal
- Call New Pig for replacement parts and filters at 1-800-HOT-HOGS or visit newpig.com

Compliance

◆ Helps you comply with federal regulation 40 CFR 261.1(c)(6) that empty cans can be recycled as scrap steel

NOTE: State and local regulations may vary.

Follow EPA Guidelines when puncturing pesticides, herbicides and other poisons.

Mount this sign on the wall at use site.

New Pig • One Pork Avenue, Tipton, PA 16684 • newpig.com • 1-800-HOT-HOGS®

83581 / 363198