

PIG Floor Protection Self-Adhesive Film

This report is offered as a guide and was developed from information which, to the best of New Pig's knowledge, was reliable and accurate. Due to variables and conditions of application beyond New Pig's control, none of the data shown in this guide is to be construed as a guarantee, expressed or implied. New Pig assumes no responsibility, obligation, or liability in conjunction with the use or misuse of the information.

PIG Floor Protection Self-Adhesive Film

Installation and Maintenance Guide

Step 1: Prepare the Floor

Surface must be clean, cured and free of moisture before installation.

Step 2: Position the Film

Place tacky side down and press the leading edge of the film against the floor to secure it.

Step 3: Roll It Out

Unroll film to the desired length and cut to size using scissors or utility knife.

Step 4: Finishing Touches

Use hands or feet to smooth film and push any air pockets to edge. For large areas, protect seams with waterproof tape (not included).

ATTENTION: Film can be left in place **up to 4 weeks** depending on conditions and traffic patterns. For longer projects, multiple applications may be required.

Floor Protection Adhesive Disclaimer

New Pig Adhesive-Backed Mats and Films are formulated to work with most common hard-floor surfaces. New Pig Adhesive-Backed Mats are not intended for use on wood flooring with stains, finishes, or coatings. If using the Carpet Protection versions of our Adhesive-Backed Mats and Films, please be sure to use only on carpeted surfaces and never on uncarpeted, hard surfaces. New Pig Adhesive-Backed Mats and Films have non-permeable barrier layers to prevent liquid pass-through and though some product construction includes a breathable film layer, may not be suitable for use on surfaces that require air curing, including, but not limited to, newly poured concrete or recently applied coatings, sealants, and finishes. All adhesive mats have some potential to leave residue or lift or discolor finish coatings, paint, and loose or pre-damaged tiles depending on the condition and age of the floors or other surfaces.

For these reasons and others, if you have questions about the suitability of New Pig Adhesive-Backed Mats and Films for your application, test a small section of mat in a discrete or non-critical area before using on larger areas. New Pig Adhesive-Backed Mats and Films should be replaced immediately if they show signs of wear or damage and should always be replaced no later than their recommended usage life.

CUSTOMER ASSUMES THE RISK THAT NEW PIG ADHESIVE-BACKED MATS AND FILMS MAY DAMAGE OR ALTER CUSTOMER'S EXISTING FLOORING OR FLOOR COVERING. NEW PIG PROVIDES NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND NO WARRANTY THAT THE USE OF AN ADHESIVE-BACKED MAT WILL BE ACCEPTABLE FOR USE ON CUSTOMER'S FLOORING OR ANY OTHER SURFACE. NEW PIG SHALL HAVE NO RESPONSIBILITY FOR, AND CUSTOMER HEREBY RELEASES AND DISCHARGES NEW PIG FROM, ANY DIRECT, INDIRECT, INCIDENTAL OR CONSEQUENTIAL DAMAGES TO OR RELATED TO CUSTOMER'S FLOORS, FLOORING MATERIAL, OR ANY OTHER SURFACES IN CUSTOMER'S DWELLING OR FACILITY. CUSTOMER IS SOLELY RESPONSIBLE FOR DETERMINING THE FITNESS AND APPROPRIATENESS OF THE USE OF NEW PIG ADHESIVE-BACKED MATS AND FILMS IN CUSTOMER'S DWELLING OR FACILITY.



New Pig

One Pork Avenue
Tipton, PA 16684-0304

newpig.com

North America: **1-800-468-4647**

Europe: **+31 (0)76 596 92 50**

China: **+86-21-400 921 5178**

PIG, PIG logo are registered trademarks in USA and other countries. See tm.newpig.com

UK: **0800 919 900**

Outside North America: **+1-814-684-0101**