

# PIG Battery Acid Neutralizing Loose Absorbent

## Instructions

---

1. Always wear proper personal protective equipment.
2. Sprinkle PIG Battery Acid Neutralizing Loose Absorbent in a circle around the spill to contain and begin absorbing and neutralizing the battery acid. The loose absorbent in this kit is designed to contain, absorb, and neutralize battery acid. This makes handling and disposal easier.
3. Pour the loose absorbent onto the rest of the spilled acid, working from the outside inward until the acid is completely covered.
4. The battery acid will be completely neutralized in approximately 5 minutes.
5. Remove the neutralized absorbent by sweeping, scooping, or shoveling it up once neutralization has occurred.
6. Product is now ready to be disposed of.

**Absorbency:** Up to 3.5 gallons of battery acid.

**Caution:** Heat may be generated during the absorption process.

**Disposal Notice:** Used absorbents can be considered hazardous and must be disposed of in compliance with local, state, and federal regulations. For information on disposal options, call New Pig.

**Ingredients:** Sodium Carbonate, Sodium Bicarbonate

**Handling and Storage:** Keep container sealed when not in use. Store in a cool, dry place.

**HMIS Rating:** Health-1, Flammability-0, Reactivity-0, PPE-B

For additional questions or information, consult the Safety Data Sheet (SDS) or contact New Pig.



**New Pig**

One Pork Avenue  
Tipton, PA 16684-0304

**newpig.com**

North America: **1-800-468-4647**

Europe: **+31 (0)76 596 92 50**

China: **+86-21-400 921 5178**

PIG, PIG logo are registered trademarks in USA and other countries. See [tm.newpig.com](http://tm.newpig.com)

UK: **0800 919 900**

Outside North America: **+1-814-684-0101**