# Draining Plug for PIG Build-A-Berm Barrier

# Instructions

## Step 1 — Determine Draining Plug placement

Determine where you want to install your Draining Plug section.

**NOTE:** We recommend choosing the lowest point of your containment area to facilitate pump-free drainage of rain, snowmelt and other innocuous fluids.

#### Step 2 — Prepare site

Using a utility knife, cut and remove a gap of your installed Build-A-Berm Barrier (fig. A). If you have a 2" berm, cut a 5" gap. For a 4" berm, cut a 12" gap. (For new installations, simply leave the appropriate size gap between two sections of Build-A-Berm Barrier.) Scrape away old caulking with putty knife (fig. B).

### Step 3 — Fit Draining Plug

Make sure the foam inserts of your Draining Plug section are pressed firmly against the PVC tubing in the middle (fig. C). Test fit the Draining Plug section in the gap of your barrier. The vinyl flaps of your Draining Plug section should overlap the Build-A-Berm Barrier sections on both sides (fig. D).

#### Step 4 — Apply caulking and adhesive

Lift out the Draining Plug section and apply silicone caulking (sold separately at newpig.com) to the ground where the Draining Plug section will be installed (fig. E). Then apply industrial-strength vinyl cement (sold separately at newpig.com) to the overlapping flaps of your Draining Plug section (fig. F).

#### Step 5 — Install Draining Plug

Install the Draining Plug section into the gap with the nylon cap on the outside of the containment area. Firmly press down to ensure a reliable seal (fig. G).

**NOTE:** The shape of the Build-A-Berm may vary by model. Installation instructions are the same for all models.

**CAUTION:** Do not drive or roll over the Draining Plug section. The weight of vehicles or handtrucks can damage the PVC tubing.

**CAUTION:** This product should only be used to drain innocuous fluids, such as rain or snowmelt. Hazardous or contaminated liquids should be collected and disposed of according to federal, state and local regulations.





newpig.com North America: 1-800-468-4647 Europe: +31 (0)76 596 92 50

UK: **0800 919 900** Outside North America: **+1-814-684-0101** 













