

PIG Storm Drain Stencil

This report is offered as a guide and was developed from information which, to the best of New Pig's knowledge, was reliable and accurate. Due to variables and conditions of application beyond New Pig's control, none of the data shown in this guide is to be construed as a guarantee, expressed or implied. New Pig assumes no responsibility, obligation, or liability in conjunction with the use or misuse of the information.

PIG Storm Drain Stencil

Instructions

1. Do not apply if raining or if rain is expected within 24 hours of application. Optimal temperature for spray paint application is between 50°F and 90°F.
2. Using a broom and/or paint scraper, remove debris from surface at curb or adjacent to the drain. PIG Storm Drain Stencil can be applied to concrete or asphalt. Do not apply on top of storm drain grate.
3. Place the stencil on flat surface. If needed, tape corners to stabilize.
4. Spray the paint approximately 8 inches from stencil surface. Depending on coverage, two applications may be required.
5. Remove stencil and wipe clean for reuse.
6. Paint cures in 60 minutes. Allow to cure during a period without rain.



New Pig

One Pork Avenue
Tipton, PA 16684-0304

newpig.com

North America: **1-800-468-4647**

Europe: **+31 (0)76 596 92 50**

China: **+86-21-400 921 5178**

PIG, PIG logo are registered trademarks in USA and other countries. See tm.newpig.com

UK: **0800 919 900**

Outside North America: **+1-814-684-0101**

503131/364928