PIG Self-Adhesive Roof Tarp

This report is offered as a guide and was developed from information which, to the best of New Pig's knowledge, was reliable and accurate. Due to variables and conditions of application beyond New Pig's control, none of the data shown in this guide is to be construed as a guarantee, expressed or implied. New Pig assumes no responsibility, obligation, or liability in conjunction with the use or misuse of the information.

Instructions for
PIG Self-Adhesive Roof Tarp

Important: Read Before Installing

- This is a ONE-TIME USE tarp and it CANNOT be reused or reapplied.
- One person can install the 10' x 10' Tarp (WTR3000); two people are recommended for installing the 10' x 20' Tarp (WTR3001)
- Make sure that the roof surface where the adhesive will be attached does not have any loose roofing material or debris that will cause the PIG Self-Adhesive Roof Tarp to move or not attach to the fixed surface.
- Do not place the PIG Self-Adhesive Roof Tarp over large holes where water can gather on top and weigh the tarp down causing it to sag. For holes larger than 24" in diameter, cover hole with plywood or other solid material before installing Tarp.
- The PIG Self-Adhesive Roof Tarp can be attached to a wet/damp roof surface but for best results it should be applied to a dry surface.

Installation Video

Scan the code to see a demonstration of the PIG Self-Adhesive Tarp being properly installed. For additional help, please call Technical Services at 1-800-HOT-HOGS® (468-4647).



- Do not stand on or depend on the PIG Self-Adhesive Roof Tarp for stability.
- The adhesive is extremely strong and pressure sensitive. Once the release liner is removed, you must be very careful that the adhesive does not touch any unintentional object, including the PIG Self-Adhesive Roof Tarp itself.
- The more pressure that can be applied during installation, the better your PIG Self-Adhesive Roof Tarp will perform. The adhesive is time-sensitive and will fully attach itself to the surface within one hour of installation.
- The adhesive can be removed without damaging the integrity of the roof by spraying multi-purpose lubricant (WD-40® is recommended) where the adhesive is attached. **Thoroughly rinse all lubricant from all surfaces immediately** to reduce any staining or degrading of the roofing material. Please follow lubricant warnings and instructions.

Instructions for a Standard Shingle or Flat Roof

WARNING: Getting onto a roof is extremely dangerous. Slipping and falling can cause bodily harm or death. Ensure you are following OSHA fall protection regulations for working on elevated surfaces while installing this product.

Step 1: Determine the damaged or faulty area of your roof, unfold your PIG Self-Adhesive Roof Tarp and position it over the area with the adhesive side down.

Step 2: Once you are confident the PIG Self-Adhesive Tarp is in the correct position, you are ready to attach your first corner. Fold back a top corner and remove both release liners to expose approximately 4–6 inches of adhesive on each edge so you can press from the top side of the PIG Self-Adhesive Tarp attaching the corner to the roof.

Step 3: With the first corner firmly attached to the roof, hold the partially removed release liner that is along the top perimeter. It is very important to not pull or stretch the PIG Self-Adhesive Tarp while contouring as this will cause it to pull away from the roof surface after installation. As you begin to remove the release liner, use your other hand to firmly press down from the top side of the PIG Self-Adhesive Tarp, attaching the exposed adhesive to the roof.

Step 4: Make sure you are contouring the tarp as you work your way across to the other corner while removing the release liner, until you are 4–6 inches from the opposite corner from which you started. Once this step is complete, you will have the top perimeter of the PIG Self-Adhesive Tarp attached except 4–6 inches from the corner where you stopped. This will allow you to remove the release liner when you start the other side.

Step 5: Repeat the same process as Steps 2 through 4 at each corner and side. All four corners and sides of the PIG Self-Adhesive Tarp are now completely attached and contoured to the roof.

Step 6: Take your thumb or palm and firmly press down around the entire perimeter once more verifying there are no gaps where wind or water can enter under the PIG Self-Adhesive Tarp.

Instructions for
PIG Self-Adhesive Roof Tarp

Instructions for Contoured or Unlevel Roof Surface, including Concrete Tile, Slate Tile, Metal Tile and Three Dimensional Asphalt Shingles.

WARNING: Getting onto a roof is extremely dangerous. Slipping and falling can cause bodily harm or death. Ensure you are following OSHA fall protection regulations for working on elevated surfaces while installing this product.

Follow Steps 1 through 4 for Standard Shingle or Flat Roof.

Step 5: Once you have the top side and one adjacent side attached, you then alternate between the two remaining sides, working 1–2 feet at a time. Working towards the corner allows slack and helps create a proper fit at completion. All four corners and sides of the PIG Self-Adhesive Tarp are now completely attached and contoured to the roof.

Step 6: Take your thumb or palm and press down around the entire perimeter once more verifying there are no gaps where wind or water can enter under the PIG Self-Adhesive Tarp.

NOTICE: New Pig guarantees the PIG Self-Adhesive Roof Tarp is free from defects and will perform as stated when above instructions are properly followed. Typical life expectancy is 3 years including shelf life, with 1 year of UV resistance when directly exposed to sunlight. The installation of the PIG Self-Adhesive Roof Tarp should be conducted by someone who is experienced in making roof repairs and is trained and proficient in safe practices for accessing, walking on, and working on roof tops. Customers should follow OSHA fall protection regulations for working on elevated surfaces while using this product.

CUSTOMER HEREBY RELEASES AND DISCHARGES NEW PIG FROM ANY DIRECT, INDIRECT, OR CONSEQUENTIAL DAMAGES TO OR RELATED TO INJURIES OR PROPERTY DAMAGES THAT OCCUR TO ANY PERSON, DWELLING, OR BUILDING DURING THE INSTALLATION OR REMOVAL OF THE PIG SELF-ADHESIVE ROOF TARP. ALL ADHESIVES HAVE SOME POTENTIAL TO LEAVE A RESIDUE OR LIFT OR DISCOLOR THE SURFACES THEY ARE ADHERED TO. CUSTOMER ASSUMES THE RISK THAT THE PIG SELF-ADHESIVE ROOF TARP MAY DAMAGE OR ALTER THE CUSTOMER'S EXISTING ROOF. NEW PIG PROVIDES NO WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE AND NO WARRANTY THAT THE USE OF AN ADHESIVE-BACKED ROOF TARP WILL BE ACCEPTABLE ON CUSTOMER'S ROOF OR ANY OTHER SURFACE.

New Pig
One Pork Avenue
Tipton, PA 16684-0304

newpig.com
North America: **1-800-468-4647**
Europe: **+31 (0)76 596 92 50**
China: **+86-21-400 921 5178**
UK: **0800 919 900**
Outside North America: **+1-814-684-0101**

PIG, PIG logo are registered trademarks in USA and other countries. See tm.newpig.com