

PIG® Pro Plus Drum Patch & Repair Kit

Description

A kit designed to patch and plug leaking drums and tanks until contents can be removed and permanent repairs are made.

GEN312-1 Kit Includes:

1 - Duct Tape	1 - #10 Screw Patch	1 - 6" L x 1.5" W x 1" H Small Wooden Wedge
4 - PIG® Repair Putty	2 - 8" x 8" Plug-N-Seal Drainstopper	1 - 6" L x 2.5" W x 1" H Medium Wooden Wedge
1 - 2.25" - 2.563" Taper Surface Plug	1 - 2" Ball Plug	1 - 6" L x 3.5" W x 1" H Large Wooden Wedge
2 - 20' L Nylon Straps	1 - #12 Screw Patch	1 - 5" L x 1" Dia Small Wooden Cone
1 - 1.625" - 2" Taper Surface Plug	1 - #14 Screw Patch	1 - 5" L x 2.25" Dia Large Wooden Cone
1 - 9" x 9" Neoprene Patch	6 - 15" x 20" PIG® Heavyweight Mat Pads (MAT203)	1 - Lead Wool
1 - 1.938" - 2.563" Taper Surface Plug	1 - .594" - 1.625" Taper Surface Plug	1 - 4" L Tapered Dowel Pin
1 - 1" -1.25" Taper Surface Plug	1 - 3.25" x 3.25" T-Patch	5 - Screws
1 - Regular Screwdriver	1 - 3.25" x 1.75" T-Patch	5 - Metal Washers
1 - #6 Screw Patch	1 - 3" x 1000' Barrier Tape Roll	5 - Rubber Washers
1 - 1" Ball Plug	1 - 1.125" - .844" Taper Surface Plug	4 - Wooden Golf Tees
1 - Phillips Screwdriver	1 - Rubber Mallet	8 - 2" x 7.5" Pieces of Lead Tape
1 - #8 Screw Patch	1 - 1" L x 1" W Small Square Tapered Peg	8 - Attention Stickers
1 - Adjustable Pliers	1 - 2" L x 2" W Large Square Tapered Peg	

Packaging: 1 Kit/Box **Color:** Black **Weight:** 27.4 lbs.

Contents:

- **Ball Plugs** – Use where the surface is deeply concave. Insert toggle through hole, hold outside end of bolt, slide ball firmly against hole and tighten wing nut until leak slows as much as possible.
- **Taper Plugs** – Use where surface is close to flat. Apply like ball plugs.
- **"T" Patches** – For cracks and irregular-shaped holes. Use like ball plugs except use "T" bolt to straddle crack.
- **Screw Patches** – For pinholes. Screw in until flow stops. Be careful not to strip out hole by tightening screw too much.
- **Lead wool and Tape** – For hairline cracks. Use sharp tool, such as a screwdriver or knife, to pack lead into crack. Start at one end and pack in lead as much as possible. Continue along the crack until it is completely plugged.
- **9" x 9" Neoprene Patch** – Apply patch to container and hold in place with adjustable nylon straps. **To use straps:** 1.) Surround container with straps. With back of metal ratchet facing container, open ratchet completely. 2.) Draw up the slack. 3.) Link hooks at the end of straps and tighten straps with the ratchet. 4.) To remove, press the release on the ratchet.
- **8" x 8" Plug Rugs** – Use as a temporary patch for larger gaping holes. Stops the flow of liquids long enough for container to be pumped or drained.
- **Wood Wedges, Pegs and Golf Tees** – Starting with larger wedges, pound as many as possible into the hole (Use enclosed rubber hammer). Wedges should swell after contacting liquid.
- **PIG® Multi-Purpose Repair Putty** – Use to plug smaller holes with or without a patch. See directions for use in Putty package.



New Pig

One Pork Avenue
Tipton, PA 16684-0304

newpig.com

North America: **1-800-468-4647**

Europe: **+31 (0)76 596 92 50**

China: **+86-21-400 921 5178**

PIG, PIG logo are registered trademarks in USA and other countries. See tm.newpig.com.

UK: **0800 919 900**

Outside North America: **+1-814-684-0101**