

# Hog Heaven™ II Modular Tile Comfort

## Specifications and Testings

---

**Type:** 100% Nitrile Rubber (20% Recycled Content)

**Thickness:** 3/4"

**Durometer:** 40–45

**Tensil:** 1100 PSI

### Cushion

**Type:** Nitrile Closed Cell Foam

**Density:** 5.5 to 7.5 lbx/ft<sup>3</sup>

**Water Absorption:** ASTM D 1667- .01 lb/sq ft maximum

**Temperature Use:** ASTM D 1056- Cold Crack: -20 degrees F  
High: 200 degrees intermittent exposure

### Testing

- Passes Flammability Standard DOC-FF-1-70
- Electrically Conductive
  - Surface to Ground 50% Relative Humidity  $1.7 \times 10^4$  OHMS
  - Surface to Ground 12% Relative Humidity  $2.9 \times 10^4$  OHMS
  - Surface to Surface 50% Relative Humidity  $2.6 \times 10^4$  OHMS
  - Surface to Surface 12% Relative Humidity  $4.9 \times 10^4$  OHMS
- ASTM C1028-96 Static Coefficient of Friction: Dry - .92 Wet = .86
- Welding Safe



**New Pig**

One Pork Avenue  
Tipton, PA 16684-0304

**newpig.com**

North America: **1-800-468-4647**

Europe: **+31 (0)76 596 92 50**

China: **+86-21-400 921 5178**

PIG, PIG logo are registered trademarks in USA and other countries. See [tm.newpig.com](http://tm.newpig.com)

UK: **0800 919 900**

Outside North America: **+1-814-684-0101**