

Hog Heaven™ III Modular Tile Comfort

Specifications and Testings

Type: 100% Nitrile Rubber (20% Recycled Content)

Thickness: 3/4"

Durometer: 40–45

Tensil: 1100 PSI

Cushion

Type: Nitrile Closed Cell Foam

Density: 5.5 to 7.5 lbx/ft³

Water Absorption: ASTM D 1667- .01 lb/sq ft maximum

Temperature Use: ASTM D 1056- Cold Crack: -20 degrees F
High: 200 degrees intermittent exposure

Testing

- Passes Flammability Standard DOC-FF-1-70
- Electrically Conductive
 - Surface to Ground 50% Relative Humidity 1.7×10^4 OHMS
 - Surface to Ground 12% Relative Humidity 2.9×10^4 OHMS
 - Surface to Surface 50% Relative Humidity 2.6×10^4 OHMS
 - Surface to Surface 12% Relative Humidity 4.9×10^4 OHMS
- ASTM C1028-96 Static Coefficient of Friction: Dry - .92 Wet = .86
- Welding Safe



New Pig

One Pork Avenue
Tipton, PA 16684-0304

newpig.com

North America: **1-800-468-4647**

Europe: **+31 (0)76 596 92 50**

China: **+86-21-400 921 5178**

PIG, PIG logo are registered trademarks in USA and other countries. See tm.newpig.com

UK: **0800 919 900**

Outside North America: **+1-814-684-0101**